



-----  
CORONADO PAINT COMPANY  
MATERIAL SAFETY DATA SHEET

1433.250B

-----  
CARCINOGENICITY

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen.

-----  
SECTION 4 - FIRST AID MEASURES

EMERGENCY FIRST AID:

IF IN EYES, Hold eyelids open and flush with a steady, gentle stream of water for 15 minutes. Get medical attention.

IF ON SKIN, immediately remove contaminated clothing or shoes, wipe excess from skin and flush with plenty of water for at least 15 minutes. Use soap if available or follow by washing with soap and water. Do not reuse clothing until thoroughly cleaned. Get medical attention. Contaminated leather articles, including shoes, cannot be decontaminated and should be destroyed to prevent reuse.

IF INHALED, remove victim to fresh air and provide oxygen if breathing is difficult. Give artificial respiration if not breathing. Get medical attention.

IF SWALLOWED, do NOT induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs. Get medical attention.

NOTES TO PHYSICIAN:

\* If more than 2.0 ml per kg has been ingested and vomiting has not occurred, emesis should be induced with supervision. Keep victim's head below hips to prevent aspiration. If symptoms such as loss of gag reflex, convulsions or unconsciousness occur before emesis, gastric lavage using a cuffed endotracheal tube should be considered.

-----  
SECTION 5 - FIRE FIGHTING MEASURES

-----  
FIRE AND EXPLOSIVE PROPERTIES OF THE CHEMICAL:

Flammability Classification . . . . . : Combustible Liquid-Class II  
Flashpoint . . . . . : > 200.0 °F  
Explosion Level . . . . . : Low - -N/A  
High - -N/A

EXTINGUISHING MEDIA

Water spray, dry chemical, carbon dioxide (CO2), alcohol foam

SPECIAL FIRE-FIGHTING PROCEDURES AND PRECAUTIONS

CAUTION. COMBUSTIBLE. Do not enter confined fire space without full bunker gear (helmet with face shield, bunker coats, gloves and rubber boots), including a positive pressure NIOSH approved self-contained breathing apparatus. Cool fire exposed containers with water.

UNUSUAL FIRE AND EXPLOSION HAZARDS

Containers exposed to intense heat from fires should be cooled with water to prevent vapor pressure build-up which could result in container rupture. Container areas exposed to direct flame contact should be cooled with large quantities of water as needed to prevent weakening of container structure.

-----  
SECTION 6 - ACCIDENTAL RELEASE MEASURES

-----  
SPILL OR LEAK PROCEDURES:

CAUTION. COMBUSTIBLE. Flush area with water to remove trace residue; dispose of flush solution, as described below.

\*\*\* SMALL SPILLS \*\*\*

Take up with an absorbent material and place in non-leaking containers for proper disposal.

-----  
CORONADO PAINT COMPANY  
MATERIAL SAFETY DATA SHEET  
-----

1433.250B  
-----

**\*\*\* LARGE SPILLS \*\*\***

Eliminate potential sources of ignition. Wear appropriate respirator and other protective clothing.  
Shut off source of leak only if safe to do so. Dike and contain.  
Remove with vacuum trucks or pump to storage vessels. Soak up residue with an absorbent such as clay, sand, or other suitable material; place in non-leaking containers and seal tightly for proper disposal.

-----  
**SECTION 7 - HANDLING AND STORAGE**  
-----

**HANDLING**

Keep liquid and vapor away from heat, sparks and flame. Surfaces that are sufficiently hot may ignite even liquid product in the absence of sparks or flame. Extinguish pilot lights, cigarettes and turn off other sources of ignition prior to use and until all vapors are gone. Vapors may accumulate and travel to ignition sources distant from the handling site; flash-fire can result. Keep containers closed when not in use. Use with adequate ventilation.

**STORAGE**

Containers, even those that have been emptied, can contain explosive vapors. Do not cut, drill, grind, weld or perform similar operations on or near containers. Do not pressurize drum containers to empty them.

**SPECIAL COMMENTS:**

Containers, even those that have been emptied, can contain hazardous product residues. Wash with soap and water before eating, drinking, smoking, or using toilet facilities. Launder contaminated clothing before reuse. Contaminated leather shoes cannot be decontaminated and should be destroyed to prevent reuse.

-----  
**SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION**  
-----

**ADDITIONAL PROTECTIVE MEASURES**

Use explosion-proof ventilation as required to control vapor concentrations. Eye wash fountains and safety showers should be available for emergency use.

**RESPIRATORY PROTECTION**

Avoid breathing dust/mists. If exposure may or does exceed occupational exposure limits, use a NIOSH-approved respirator to prevent overexposure. Avoid breathing vapors, which may be produced under some conditions such as heating or applications of uncured product in large surface areas (e.g., flooring and painting). Avoid breathing aerosols and mists which may be formed by various methods of application.

**EYE PROTECTION:**

Avoid contact with eyes. Wear safety glasses or goggles as appropriate.

**PROTECTIVE GLOVES:**

Avoid prolonged or repeated contact with skin. Wear chemical resistant gloves and other clothing, as required, to minimize contact.

-----  
**SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**  
-----

Appearance . . . . . : VERY LIGHT YELLOW COLOR  
Physical State . . . . . : LIQUID  
Vapor Pressure . . . . . : -N/A  
Vapor Density . . . . . : -N/A  
Boiling Point Range . . . . . : Lower - -N/A      øf

CORONADO PAINT COMPANY  
MATERIAL SAFETY DATA SHEET

1433.250B

	Higher - 400.0 °F
Specific Gravity . . . . .	: 1.021
Weight per Volume . . . . .	: 8.5000 LB/GL
VOC - Total (lbs./gal) . . . . .	: .000
Evaporation Rate . . . . .	: .000 (n-Butyl Acetate = 1)
Volatile by Weight . . . . .	: .0000
Volatile by Volume . . . . .	: .0000

SECTION 10 - STABILITY AND REACTIVITY

INCOMPATIBILITIES (Materials to Avoid)

This product can react violently with strong oxidizing agents and strong acids.

HAZARDOUS POLYMERIZATION

Will not occur.

CONDITIONS TO AVOID

Avoid heat and flames. Can react vigorously with strong oxidizing agents, strong Lewis or mineral acids, and strong mineral and organic bases (especially primary and secondary aliphatic amines). Reaction with some curing agents may produce considerable heat.

HAZARDOUS DECOMPOSITION PRODUCTS

Carbon monoxide, aldehydes, acids, and other organic substances may be formed during combustion or elevated (> 500 Deg F) temperature degradation.

STABILITY: Stable.

SECTION 11 - TOXICOLOGICAL INFORMATION

No data at this time.

SECTION 12 - ECOLOGICAL INFORMATION

No data at this time.

SECTION 13 - DISPOSAL CONSIDERATIONS

DISPOSAL CONSIDERATION

Consult an expert on disposal of recovered product and ensure conformity to local disposal regulations.

SECTION 14 - TRANSPORT INFORMATION

DOT HAZARD CLASS . . . . . : NOT REGULATED (In containers less than 119 gallons or 450 liters via surface transportation).  
COMBUSTIBLE LIQUID (In containers of more than 119 gallons capacity) for surface shipments within the U.S. and Canada, and apply the DOT information, listed below:

DOT SHIPPING NAME . . . . . : PAINT  
DOT PACKAGING GROUP . . . . . : PG III  
DOT LABEL . . . . . : NONE  
DOT PLACARD . . . . . : NONE  
UN/NA NUMBER . . . . . : UN1263

SECTION 15 - REGULATORY INFORMATION

-----  
CORONADO PAINT COMPANY  
MATERIAL SAFETY DATA SHEET

1433.250B

-----  
U.S. FEDERAL REGULATORY INFORMATION

TSCA SECTION 8(b) - INVENTORY STATUS:

All components of this product are either listed on the U.S. Toxic Substances Control Act (TSCA) inventory of chemicals or are otherwise compliant with TSCA Regulations.

SARA 313 TOXIC CHEMICALS:

This product contains NONE of the substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

-----  
SECTION 16 - OTHER INFORMATION

-----  
Prepared by . . . . . : INSL-X / CORONADO PAINT COMPANY  
Date of issue . . . . . : 03/01/2006  
Last Revision Date . . . . . : NONE  
MSDS Prepared for . . . . . :

MSDS Last Prepared . . . . . : NONE  
HMIS Rating:           Health- 3           Flammability- 1  
                          Reactivity- 0

\*\*\*\*\*

This Material Safety Data Sheet conforms to the Hazard Communication Standard, 29 CFR 1910.1200(g) (4).

The above information pertains to this product as currently formulated and is based on the information available, as of this date. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

\*\*\*\*\*

Abbreviations used: int.- interior; ext.- exterior; MSDS - Material Safety Data Sheet; HMIS - Hazardous Materials Information System; CAS - Chemical Abstracts Services; pct - percent; wt - weight; mm Hg - millimeters of mercury; F - Fahrenheit; ACGIH - American Conference of Governmental Industrial Hygienists; TLV - Threshold Limit Value; OSHA - Occupational Safety and Health Administration; PEL - Permissible Exposure Limit; TWA - Time-Weighted Average; STEL- Short Term Exposure Limit; N/A- Not applicable IARC - International Agency for Research on Cancer; NE - Not established NTP - National Toxicological Program; CFR - Code of Federal Regulations; OSHA - Z 29CFR 1910, Subpart Z; VOC - Volatile Organic Compounds; TCC - Tag Closed Cup; LEL - Lower Explosive Limit; Mg/m3 or Mg/Cu M - milligram per cubic meter; mppcf - millions of particles per cubic foot; ppm - parts per million; NIOSH - National Institute of Occupational Safety and Health; MSHA - Mine Safety and Health Administration; CNS - Central Nervous System.